





#### **FEATURES**

- HDMI video and audio transmission via wireless WIFI, up to 200 meters;
- HD video signal resolution up to 1920 \* 1080 @ 60
  Hz
- HDMI 1.3 compatible
- Special format H.264 is used to compress and decompress video, effectively improve the transfer efficiency, to ensure that the playback fluency
- In accordance with standard 1.2 HDCP, high-bandwidth digital content protection technology
- Supports external remote infrared extension, easy to operate the remote device
- Transmitter support one channel LOOP OUT
- Able to automatically identify and configure a variety of display mode
- Built-in automatic balance system, the picture is fluent, clear and stable
- Simple and convenient installation, plug and play, do not need to set up

Newbridge® HDMI extender through wireless WIFI signal transmission HD audio and video signal, at the same time, with infrared extensions to make remote control more convenient. The equipment has excellent image processing and transmission capacity, makes signal transmission more smooth and steady, is a kind of economic and efficient way of HDMI signal extension







### **Specifications**


Parameter		Description
Video	Standards	HDMI 1.3; HDCP 1.2
	Compressed format	H.264
	Maximum pixel clock	165MHz
	Maximum data rate	6.75Gbps
	Resolution	Max: 1920X1080p@60Hz
	Connector	HDMI-A
	Impedance	100Ω
	Recommend HDMI	Less than 5 meters, when 1920 x1080p @ 60 Hz
	maximum	
	input/output range	
IR	Interface	3.5mm Stereo audio socket
	Signal direction	Unidirectional
	Signal type	Digital
	IR frequency	20-60kHz
	Radio Frequency	24dbm
WIFI	power	
	Wireless standards	802.11a/n
	signal direction	Unidirectional
	Radio frequency	5.15-5.825GHz
	Transmission distance	Undisturbed environment 200M
Other	Power	Adapter:DC 5V
	Power dissipation	MAX 10W
	Temperature	Operating: -5°C~+70°C
	Humidity	Operating : 5% ~ 90%
	Size	112.6*95*18.2mm
	Warranty	1 year free warranty







#### **Panel**

#### **Transmitter:**











Port name	Description		
HD IN / OUT	HDMI signal input/output		
IR IN / OUT	IR signal input/output		
DC 5-12V	Power adapter socket		
RESET	Reset button (The absence of technical staff guidance, please do not key)		
LED indicator	Description		
STA	Connect light		
PWR	System power indicator		

ND8110HW-100



### **Application**



#### **Order Information**

Part No	Description of product	Unit
	HDMI video and audio transmission via wireless WIFI, up to 200	pair
ND8110HW-100	meters;	
	HD video signal resolution up to 1920 * 1080 @ 60 Hz	