

# 4K@60 HDMI Extender

ND8310HE-50



## FEATURES

- Transmits HDMI video and audio signals up to 50M over a single CAT6 cable;
- Support video resolution up to 3840\*2160@60Hz signa ;
- Supports screen formats YUV444 and RGB444 ;
- Compliance with HDMI 2.0 and HDCP 2.2 standard ;
- Standard Ethernet IEEE-568B connection for easy installation ;
- High compatibility, can auto-match source and display device ;
- Built-in automatic adjustment system, make the image smooth, clear and stable ;
- Simple to install, plug and play



The extender provides extension of HDMI signals long distances up to 50m over a single CAT6 cable. It supports high resolution up to 3840\*2160@60Hz and Infrared signal transmission. The extender can use for a wide range of applications requiring long distance transmission of high resolution with high quality by its good stability and powerful security.

## Specifications

	Parameter	Description
Video	Standards	HDMI 2.0; HDCP 2.2
	Maximum pixel clock	340MHz
	Maximum data rate	18Gbps
	Maximum resolution	3840*2160@60Hz
	Connector	HDMI-A
	Impedance	100Ω

# 4K@60 HDMI Extender


ND8310HE-50




UTP	Interface	RJ45
	Transmission distance	CAT6 - up to 50M at 4K@60 ,
Other	Power supply	The power adapter: DC 5V
	Power dissipation	MAX 3W
	Temperature	Operating: -5°C ~ +70°C
	Humidity	Operating: 5% ~ 90%
	Dimension	81*45*23mm
	The warranty	1 year free warranty

## Panel

### Transmitter:



### Receiver:




Port name	Description
DC 5V	DC 5V/1A power input
HD IN/HD OUT	HDMI signal input/output
UTP	RJ45 port connect cat6
LED indicator	Description
STA	HDMI signal status indicator, HDMI signal is normal , the light is always on
PWR	Power indicator, after the power is turned on, the light is always on

# 4K@60 HDMI Extender

ND8310HE-50



## Application



## Order Information

Part No	Description of product	Unit
ND8310HE-50	HDMI extender,50m,HDMI 2.0; HDCP 2.2, 5V1A/DC, up to 3840*2160@60Hz	pair