

FEATURES

- 16× gigabit PoE+ ports and 2× gigabit SFP
- Supports PoE power up to 30W for each PoE port, all power up to 500W
- IEEE 802.3af/at PoE standards
- Support intelligent opening, automatic configuration of the network, topology graphic display
- Supports quad binding, ARP/IP/DoS protection, 802.1X authentication
- Supports IEEE 802.1Q VLAN, QoS, ACL, Spanning Tree, Multicast, IPv6
- Supports port security, port monitoring, port isolation
- Supports Web-based network management, CLI command line, SNMP



NB-GS3218FP is NEWBRIDGE self-developed full Gigabit L2 managed ring PoE switch. The switch has 16× 10/100/1000Mbps PoE+ ports + 2× 1000Mbps SFP Slot, where 1-16 100/1000 Mbps downlink power ports all support powering PoE network cameras via UTP Category 5 and above unshielded twisted pair cables. 16 10/100/1000Mbps adaptive RJ45 downlink ports all support 802.3af/at standard PoE power supply. The maximum PoE output power of the whole machine is 500 W, and the maximum power supply power of individual ports is 30W.

The NB-3218FP is a full thousand Layer 2 managed PoE switch, Using a new generation of high-performance hardware and software platform to provide flexible, cost-effective full Gigabit access and uplink ports, support for complete security protection mechanisms, perfect ACL/QoS policy and flexible VLAN function, easy to manage and maintain, to meet the user's network for network equipment, easy to manage, high security, low-cost network requirements for campuses, hotels, and business parks network access, convergence of a variety of application scenarios.

Specifications

Model	NB-GS3218FP	
Standards	IEEE 802.3i 、IEEE 802.3u 、IEEE802.3ab 、IEEE802.3x 、 IEEE802.3az, IEEE802.3af 、 IEEE802.3at	
Number of Ports	16 x 10/100/1000Mbps ports 2 x 1000Mbps SFP ports 1x Console port	
Network Media (Cable)	10Base-T: UTP category 3, 4, 5 cable (maximum 100m) 100Base-Tx: UTP category 5, 5e cable (maximum 100m) 1000Base-T: UTP category 5e, 6 cable (maximum 100m) 1000Base-X:MMF,SMF	
Transfer Method	Store-and-Forward	
MAC Address Table	8K	
Switching Capacity	36Gbps	
Packet Forwarding Rate	26.784Mpps	
Packet Buffer	4.1Mbit	
PoE Ports(RJ45)	16x PoE ports compliant with 802.3at/af	
Power Pin Assignment	1/2(+),3/6(-)	
PoE Budget	500W@100~260VAC,50/60HZ	
Indicators	Per Device	Power, System
	Per Port	Link/Activity,
Power Supply	100~240VAC,50/60HZ,500W	
Power Consumption	Maximum(PoE on):500W	

Dimensions (W×D×H)	310mm*183mm*45mm
Installation	Guide rail/wall mount
Environment	Operating Temperature: 0°C~45°C Storage Temperature: -40°C~70°C Operating Humidity: 10%~90% non-condensing Storage humidity: 5%~90% non-condensing

Software Specification

L2 Features		Support
MAC Address Table		8K
Jumbo Frame		10K (10000)
Flow Control	802.3x (Full-duplex)	Yes
	Back-Pressure (Half-duplex)	Yes
Spanning Tree	IEEE 802.1D (STP)	Yes
	IEEE 802.1w (RSTP)	Yes
	IEEE 802.1s (MSTP)	16 instances
	Auto Edge Port	Yes
	BPDU Filtering	Yes
	ERPS	Yes
	Self Loop Detection	Yes
Link Aggregation	IEEE 802.3ad LACP	Yes
	Static Trunk	Yes
	Max. Group	8
	Max. Ports/Group	8
	Traffic Load Balancing	Yes
Static Routing		Yes (IPv4/IPv6)
Address Resolution Protocol (ARP)	Static ARP	Yes
VLAN		
	Static VLAN	256
	Port-based	Yes
	IEEE 802.1Q Tagged-based	Yes

16-Port Gigabit+2-Port Gigabit SFP L2

NB-GS3218FP



VLAN	Protocol-based	8 groups
	MAC-based	256
	OUI Mode (Auto/Manual)	16 OUI
Voice VLAN		
Surveillance VLAN	OUI Mode (Auto/Manual)	16 OUI
QinQ (IEEE 802.1ad)	Basic	Yes
GARP VLAN Registration Protocol (GVRP)		Yes
Multicast		
Common	Multicast Groups	256
	Immediate Leave	Yes
	Static/Forbidden Router Port	Yes
	Static/Forbidden Forward Port	Yes
	Filtering	128 profiles
	Throttling	Yes
IGMP Snooping	IGMP v1/v2	Yes
	IGMP v3 Basic (BISS)	Yes
	IGMP v2/v3 Querier	Yes
MLD Snooping	MLD v1/v2	Yes
Multicast VLAN Registration (MVR)		Yes (IPv4)
QoS Features		
Priority Queue		8 queues/port
Queue Scheduling	WRR	Yes
	WFQ	Yes
	Strict Priority	Yes
	Hybrid(WRR+SP or WFQ+SP)	Yes
Class of Service	Port-based	Yes
	802.1p	Yes
	IP TOS Precedence	Yes
	IP DSCP	Yes
Trusted QoS		Yes
Rate Limit	Port-based (Ingress/Egress)	Yes
Access Control List (ACL)		

16-Port Gigabit+2-Port Gigabit SFP L2

NB-GS3218FP



Access Rules		1024
ACL Type	L2/L3/L4	Yes
	MAC-based	512
	IPv4-based	
	IPv6-based	
PoE Function	Power	Yes
	Current	Yes
	Voltage	Yes
	PoE Watch Dog	Yes
Security		
AAA	Authentication	Yes
TACACS+		8
RADIUS		8
Authentication Manager	IEEE 802.1X	Yes
	MAC Auth	Yes
	Web Auth	Yes
	Guest VLAN	Yes
	Port-based	Yes
	Host-based	Yes
Account Manager	Local Authentication	Yes
	Multiple User Account	8
	Multi-Level Security (Manager/Operator)	Yes
	Password Recovery Procedures	Yes
Management Access	Management VLAN	Yes
	Management ACL	256
SSL	SSLv2	Yes
	SSLv3	Yes
	TLSv1	Yes
WebUI	HTTPS	Yes
CLI	SSH v1/v2	Yes
Port Security	Dynamic Lock	256
Storm Control	Broadcast	Yes
	Unknown Multicast	Yes
	Unknown Unicast	Yes

16-Port Gigabit+2-Port Gigabit SFP L2

NB-GS3218FP



Spanning Tree	BPDUGuard	Yes
Protected Port (Port Isolation)		Yes
Black Hole MAC		Yes
CPU Defence Engine		Yes
DoS Prevention		Yes
DHCP Snooping (with Option 82)		Yes
Dynamic ARP Inspection		Yes
IP Source Guard		256
IP/MAC/Port Binding (IMPB)		Yes
Dynamic VLAN Assignment		Yes
IPv6		
IPv6 Host	Auto Configuration	Yes
	Static IPv6 Address and Prefix Length	Yes
	Static IPv6 Default Gateway	Yes
	IPv6 Neighbor Discovery (ND)	Yes
	IPv6 Duplicate Address Detection	Yes
	ICMPv6	Yes
IPv6 Application	HTTP/HTTPS	Yes
	TELNET	Yes
	SSH	Yes
	SNMP	Yes
	TFTP	Yes
	Syslog	Yes
	PING	Yes
	DHCPv6	Yes
Management		
CLI	Console	3 sessions
	Telnet (RFC854)	
WebUI	HTTP	Yes
SNMP	v1	Yes
	v2c	Yes
	v3	Yes
Firmware Upgrade/Backup		Yes

16-Port Gigabit+2-Port Gigabit SFP L2

NB-GS3218FP



File Management	Dual Images	Yes
	Configuration Download/Backup	Yes
	Multiple Configurations	Yes
Upload/Download	TFTP (RFC783)	Yes
	HTTP	Yes
	UART	Yes
Time Management	Local	Yes
	SNTP	Yes
Port Management	Friendly Port Name (Port Description)	Yes
	Error Disabled Recovery	Yes
Line Management	Console	Yes
	Telnet (RFC854)	Yes
	SSH v1/v2	Yes
DHCP	Client	Yes
DNS	Client	Yes
Software Reset Button		Yes
EEE (802.3az)		Yes
RMON Management		32 entries / type
Discovery		
IEEE 802.1AB Link Layer Discovery Protocol (LLDP)		Yes
ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)		Yes
Diagnostics		
Mirroring	Port-based (Many to One)	4 sessions
Syslog (RFC3164)	Local RAM	Yes
	Local Flash	Yes
	Remote Server	8
System Diagnostics	CPU Utilization	Yes
	Memory Utilization	Yes
	Port Utilization	Yes
	Technical Support Log	Yes
Port Diagnostics	Cable Test	Yes
	Fiber Module Status	Yes

16-Port Gigabit+2-Port Gigabit SFP L2

NB-GS3218FP



Network Diagnostics	Ping Test	Yes
	Traceroute	Yes
UDLD		Yes
MIB		
RFC1213 MIBII (System & Interface groups)		Yes
RFC2819 RMON I (1,2,3, & 9 groups)		Yes
RFC1215 Generic Traps		Yes
RFC1493 Bridge		Yes
RFC2674 Bridge MIB Extensions		Yes
RFC2737 Entity		Yes
RFC3635 Ethernet-Like		Yes
RFC2863 Interface Group		Yes
SNMP-Community-MIB		Yes
SNMPv3-MIB		Yes

Order Information

Part No	Description of product	Unit
NB-GS3218FP	2*1000M SFP slot, 16*10/100/1000 Base-Tx L2 managed PoE Switch ,PoE Standard: IEEE 802.3af/at.	pc